

DRIVE OVER CONVEYORS



SA 20 & SA 30 DRIVE OVER TRANSFER CONVEYORS

EASILY SWING FROM
HOPPER TO HOPPER



ULTRA LOW DRIVE OVER HEIGHT
20 AND 30 IN BELT WIDTHS
UP TO 20,000+ BPH

Performance:	SA 20	SA 30
Bushels Per Hour	13,000	20,000
Gallons Per Minute @ 2000 PSI	20	25
Dimensions:		
Belt Width	20"	30"
Belt Length	48'	48'
Conveyor Length	27'	27'
Spout Discharge Height	33"	26"
Total Weight	1460 lbs	2480 lbs
Tire Size	18.5x10"	20.5x10"
Drive-Over Frame Height	2.5"	2.5"
Drive-Over Frame Width in Feet	10.5'	10.5'
Optional Frame Extension	1'	1'
Adjustable Hopper	36"x128"	46"x128"
Features:		
Low Profile Drive-Over Frame	Standard	Standard
Automatic Emergency Shut-off	Standard	Standard
Self Cleaning Rollers	Standard	Standard
Swinging Drive Wheel	Standard	Standard
Adjustable Hatch	Standard	Standard
Adjustable Frame	Standard	Standard
Adjustable Belt Tension	Standard	Standard
Options:		
Hydraulic Drive	Standard	Standard
Electric Drive	Optional	Optional
Gas Drive	Optional	Optional



DRIVE OVER CONVEYORS

SEAN MCGIVERN
NORTH VALLEY AG & MILL

EMAIL: sean@northvalleyagme.com
WEB: www.NorthValleyAgMe.com

PH: (519) 374-9300 or (902) 393-9097

