

The LA-BG belt grader for small-scale use is designed for separation of rough surface seeds from smooth surface seeds – e.g. vegetable seeds such as beet seeds and flower seeds such as primula and begonia seeds



STANDARD FEATURES:

- Inlet with capacity shutter and vibrator feeder with start/stop and potentiometer.
- Smooth PVC belt.
- Transparent guard plate over the inlet section of the belt.
- Manually adjustable belt speed.
- Remote control for adjustment of belt inclination.
- Outlet hopper for round product and end outlet hopper for other products; with manually adjustable product divider.
- Motor for belt drive with built-in frequency converter, including start/stop and potentiometer.
- Motor for vibrator feeder.
- The machine is of steel construction.

OPTIONS:

- Special belt to separate seeds with different types of surface (black soft belt)
- Indented PVC belt (white)
- Autotransformer for 110 V, 60 Hz

TECHNICAL SPECIFICATIONS:

	LA-BG
Belt width mm	600
Motors V	1 x 230
Motor for belt drive kW	0.25
Motor for vibrator feeder kW	.05

DISTINGUISHING ADVANTAGES:

- Transparent guard plate over the inlet section of the belt to avoid seed jumping
- Electrical controls for easy connection into a 230 V outlet; autotransformer for 110 V also available
- Easy clean-down when changing from one product to another
- Low maintenance costs