

STATE OF THE ART AUTOMATIC PALLET POSITIONER NOW ADJUSTABLE WITHOUT CHANGING AIR PRESSURE!



STANDARD FEATURES:

- Self leveling design automatically keeps the top of the load at a convenient working height to help eliminate bending and improve productivity
- Integral rotator ring helps eliminate reaching and stretching
- Captive air operation eliminates cumbersome mechanical springs and gives more controlled (dampened) movement of the platform
- A three position EZ Adjust knob allows adjustment of the collapsed capacity without changing air pressure
- Secured ball bearing center pivot of the 43" diameter rotator ring provides smooth, even rotation
- Pressure relief valve prevents excess pressure build-up
- Surfaces are phosphatized and powder coated with a high quality polyester for a lasting, durable finish
- Rollers are entrapped in the base frame and platform for added stability
- A full coverage finger guard eliminates pinch points between the rotator underside of the rotator ring and the bearings
- Integral maintenance blocks
- EZ Loaders arrive at your facility fully assembled - just add air!
- Easily transported with a fork truck or via optional portability packages



UNIQUE PATENT-PENDING,
SELF-CONTAINED PNEUMATIC
SYSTEM OFFERS UNSURPASSED
PERFORMANCE



EZ-ADJUST KNOB PROVIDES UP TO
1200 LBS OF CAPACITY ADJUSTMENT
WITH THE TURN OF A KNOB



HINGED MAINTENANCE BARS
FOR ADDED SAFETY



ROLLERS ARE ENTRAPPED IN THE
BASE FRAME AND PLATFORM FOR
ADDED STABILITY

MODELS:



MODEL NAME	DESCRIPTION
EZ LOADER	Standard powder coated finish
EZ LOADER-E	FDA compliant powder coated finish with stainless solid round top
EZ LOADER-SS	Grade 304 stainless steel with electro-polished finish
EZ LOADER-2848	Fixed non-rotating platform 28" x 48"
EZ LOADER-3648	Fixed non-rotating platform 36" x 48"

ACCESSORIES:



BRAKE PREVENTS ROTATOR RING FROM TURNING



ACCORDION BELLOWS SKIRTING



SOLID ROTATING TOP



CART PORTABILITY WITH 2 SWIVEL AND 2 FIXED CASTER WHEELS



OVERSIZE ROTATING PLATFORM



EASILY MOVED WITH A FORK TRUCK

ACCESSORIES CONTINUED:

MODEL NAME	DESCRIPTION
EZ-BRK	Rotator ring brake to prevent rotation
EZ-ABS	Accordion bellows skirting with frame
EZ-SLP	Semi - live portability for moving unloaded lift (2 wheels & dolly handle)
EZ-CART	Cart portability with 2 swivel and 2 rigid wheels (add 7" to lowered height)
EZ-SRT	Solid 43" diameter round top
EZ-4444	Oversize rectangular rotating platform (44"x44")
EZ-4448	Oversize rectangular rotating platform (44"x48")
EZ-4848	Oversize rectangular rotating platform (48"x48")
EZ-SRT-DNT	Solid 43" diameter round top with 90 degree detents
EZ-4444-DNT	Oversize rectangular rotating platform (44"x44") with 90 degree detents
EZ-4448-DNT	Oversize rectangular rotating platform (44"x48") with 90 degree detents
EZ-4848-DNT	Oversize rectangular rotating platform (48"x48") with 90 degree detents

TOP SHIELD ELIMINATED PINCH POINTS

STANDARD TOP FRAME COVER – PROTECTS HANDS AND FINGERS


FULL FINGER GUARD PROTECTS OPERATORS HANDS & FINGERS




SAFETY ANGLE ELIMINATES PINCH POINTS

PATENTED SELF CONTAINED PNEUMATIC SYSTEM OFFERS UNSURPASSED PERFORMANCE

COMPLIES WITH ALL MACHINERY DIRECTIVE 2006/42/EC SAFETY REQUIREMENTS





EZ LOADERS ARE CE APPROVED




EZ ADJUST KNOB PROVIDES UP TO 1200 LBS OF CAPACITY ADJUSTMENT WITH THE TURN OF A KNOB

PERFORMANCE CHART:

UNLOADED AIR PRESSURE SETTING (PSI)			
	TOTAL PALLET WEIGHT (LBS)		
	LIGHT WEIGHT POSITION	MEDIUM WEIGHT POSITION	HEAVY WEIGHT POSITION
12	250-450	725-800	900-1000
15	550-600	800-900	1100-1200
20	700-750	1000-1100	1350-1450
25	850-925	1200-1300	1550-1700
30	1000-1100	1375-1525	1775-1950
35	1150-1250	1600-1750	2000-2200
40	1300-1450	1825-2000	2300-2500
45	1475-1625	2000-2200	2550-2750
50	1625-1775	2200-2400	2800-3000
55	1775-1950	2375-2575	3050-3275
60	1950-2100	2800-2825	3300-4000

Based on a standard EZ Loader with rotator ring and no options.
Addition of solid tops, etc will vary the PSI req.

SPECIFICATIONS:



- (A) ROTATOR RING DIAMETER = 43.0 inches (1092 mm)
- (B) LOWERED HEIGHT = 10.5 inches (267 mm)
- (C) RAISED HEIGHT = 30.5 inches (775 mm)
- (D) BASE FRAME LENGTH = 49.0 inches (1245 mm)
- (E) BASE FRAME WIDTH = 24.3 inches (617 mm)

Minimum Self Leveling Capacity = 250 lbs (113 kgs)
Maximum Self Leveling Capacity = 3500 lbs (1588 kgs)
Maximum Load Capacity = 4000 lbs (1814 kgs)
Travel = 20.0 inches (508 mm)
Air Pressure Capacity Adjustment = Infinite
(10 – 60 psi / 0.7 – 4.1 bar)
On-board Capacity Adjustment = 3 position knob
(light – medium – heavy)